

iProbe Plus Scanning Probe



Secure data storage, reporting, and traceability in the palm of your hand.



Key Features

- Filter scan report traceability
- On-board data storage
- Easy data transfer via USB
- Large, 4.3-inch color touchscreen
- Compatible with existing 2i photometers, no firmware update required (“plug and play”)*
- Optional password protection

Key Benefits

- Supports 21 CFR Part 11 compliance
- Enhances data integrity and quality control
- Eliminates the need to connect to a computer or printer for real-time data output
- Improves efficiency and saves time

* 2i main unit must be at firmware rev 4.6.1 or higher



IProbe Plus Scanning Probe

Quality Control, Traceability, and Security

The iProbe **Plus** creates a unique record of each filter scanned. Each record includes key identifiers (IDs) and important scan data for quality control and leak scan traceability.

- | | |
|---|---|
| Scan Traceability IDs | Additional Data for Each Scan |
| <ul style="list-style-type: none"> • Job • Room • Filter • Technician | <ul style="list-style-type: none"> • Max % leakage • Effective scan time • Every alarm instance recorded • Pass/fail recorded for each scan |

- **Supports 21 CFR Part 11 compliance** through encryption, password protection, and data protection. Filter leak data saved on the iProbe **Plus** cannot be altered.
- Offers optional **password protection** of critical parameters such as date/time, deletion/removal, and **encryption** of the test data.
- **Reporting:** Can save approx. 150,000 scans. Each saved leak scan is in a **.CSV and .PDF** file format for easy analysis. The files can be removed via a USB-A stick.

Efficiencies, Ease of Use, and Safety

Upstream/Downstream/Clear Controls:


The iProbe **Plus** allows the user to actuate the upstream/downstream/clear valves through the touchscreen (patented feature). This improves efficiency and safety by eliminating the need to actuate the valves through the 2i base unit.

Additional User Conveniences:


- All firmware updates are installed via USB-A memory stick
- Unique 10-second “rewind” button prevents the saving of accidental alarm events (patent pending)
- Ergonomic handle with finger grooves and thumb rest
- Important information displayed on screen, such as Max % Leakage; Filter ID; Elapsed Scan Time



Scanning Screen



Scan Traceability IDs



Security Settings



Ergonomic Handle



Scan for more details and a video demonstration

Item Description	Part Number
iProbe Plus (only)	9300538
iProbe Plus / 2i small ensemble (120V)	9300529
iProbe Plus / 2i small ensemble (240V)	9300530



Protecting People, Products & Critical Infrastructure

REV A

USA +1 410.363.9696
UK +44 (0) 1462 676446

info@atitest.com
www.atitest.com

